



Competence Center for Gas Exchange



”Charging for the future”






Detecting compressor surge using the Hurst exponent

Bertrand Kerres

Supervisors: Andreas Cronhjort & Mihai Mihaescu



VOLVO



BorgWarner



Topics

- Investigate the Hurst exponent as compressor surge indicator:
 - General applicability
 - Sensor location
- Algorithm for early detection based on different orders of the Hurst exponent




What is the Hurst exponent

- Hurst exponent H gives information about the scaling and long-term trends for self-similar data

$$x(t) \rightarrow a^H x(at)$$

- Idea: random walk based on pressure data
 - At stable operation, depends on sampling length due to e.g. noise, turbulence
 - Near surge, independent of sampling length since the pattern repeats itself



Ex.: Random walk with step size $\sim N(0,1) \rightarrow H=0.5$

(see rescaled data axis)



Multifractality – a generalized Hurst exponent

- Hurst exponent of different orders $q \in \mathbb{R}$
- Monofractality: scaling law is the same for large and small amplitude oscillations




$$H^q \neq f(q)$$

- Multifractality: scaling laws for large and small amplitude oscillations differ

$$H^q = f(q)$$


Results: Hurst exponent vs Std Deviation

(c) E. Guillou (2011)



- Honeywell GT40 (HD turbocharger, ported shroud), N=64 krpm:
 - Hurst exponent has better properties as warning indicator
 - Sensors near the outlet and upstream tongue better suited

Results: Compressor Map



- Hurst exponent (based on outlet pressure):
 - $H > 0.5$ at peak efficiency
 - $0.15 < H < 0.5$ at low mass flows
 - $H < 0.15$ in deep surge
- Monofractal – multifractal distinction has potential as early warning



Summary and Outlook

- Hurst exponent as surge indicator:
 - + Well-defined limit $H=0$ for pure oscillations
 - + Potential as early warning indicator
 - Many tuning parameters for the algorithm
 - Complexity of the concept
- Future plans:
 - Test on engine intake geometry (filter, resonators)
 - Artificial pressure pulse at outlet (simulate intake valves)



Competence Center for Gas Exchange



”Charging for the future”

